



## LUMALINE I LE6535.2


### Linear Lighting System

#### Description

The LUMALINE linear lighting system is designed to deliver balanced, comfortable illumination with a clean and timeless aesthetic. Featuring a slim suspended profile and uniform light output, it provides reliable ambient lighting without visual complexity. LUMALINE focuses on consistency and simplicity, making it an ideal solution for everyday lighting needs across offices, classrooms, retail environments, and hospitality spaces. Its straightforward design and even distribution of light allow it to blend naturally into interiors, supporting the space without competing with the architecture.

#### Colour

Black/White



#### TECHNICAL DATA

##### Light source

Light source: LED SMD  
 Output (W): 40W  
 Color temperature: 3000K/3500K/4000K/5000K  
 CRI:  $\geq 80/90$   
 Delivered Lumen: 4000lm  
 Control : On Off / Dali / 0-10V  
 Efficacy: 100lm/W  
 Life Time: 50000h  
 MacAdam steps: 3  
 UGR: <17


##### Physical Attributes

TrimType : N/A  
 Dimension : L1200xW65xH35mm

##### Electrical Features

Input Voltage : 100-240VAC  
 Driver Type : Remote

#### Photometric Distribution Curve



Various technical specifications, length, colors, and finishes are available upon request.

